

High protection against burglary



High protection against fire



REGENT

FIRE & BURGLARY RESISTANT SAFE

KEY FEATURES

- Double-walled safe with a specially formulated barrier material to resist fire and conventional tool attacks.
- Standard configuration comes with two adjustable shelves and a bottom drawer.
- Designed to resist fire for 60 minutes as per JIS Standards.
- A dual key lock can be customized with the option of an electronic or combination lock for enhanced protection.
- Strong movable shooting bolts.
- Protects cash, valuables, records and documents.

PAN INDIA SERVICE AND INSTALLATION NETWORK

| Model | External Height (mm) | External Width (mm) | External Depth (mm) | Internal Height (mm) | Internal Width (mm) | Internal Depth (mm) | Capacity (litres) | Net Weight (kg) | No. of Drawers |
|-------|-------------------------|------------------------|------------------------|-------------------------|------------------------|------------------------|----------------------|--------------------|-------------------|
| 94 | 895 | 536 | 510 | 762 | 406 | 305 | 94 | 230 | 1 |
| 189 | 1048 | 638 | 611 | 915 | 508 | 406 | 189 | 325 | 1 |
| 314 | 1654 | 638 | 611 | 1524 | 508 | 406 | 314 | 530 | 1 |

Standard door is right hung. Gunnebo policy is one of constant improvement. We reserve the right to alter specifications without prior notice.

LOCK OPTIONS



Key lock



Combination lock



Electronic lock

PRODUCT BENEFITS

- Tested as per JIS standards for fire resistance and provides burglary resistance against conventional tools.
- Monolithic door construction for superior strength and protection.
- Convenient and user-friendly solution with different size options.
- Option of smart alarm system for enhanced security.
- This safe is ideal for protecting cash, valuables, and important documents.

Authorised Steelage Partner



Svanz International Pvt. Ltd. Punjab, Haryana, HP, J&K Plot no. 990, Sector - 82, Mohali For enquiry call us at: 9041690417, 9855100370 Or email at sales@svanz.com

www.Svanz.com

^{*}Tolerance on weight +/- 10% & Tolerance on dimensions is +/- 5 mm

^{*}Conditions Apply